

STAIR NOSING AUSTRALIA

Contact : Daphne 0422 803 365

email: daphne@stairnosingaustralia.com.au

STAIRNOSING 12 series-stair nosing suitable for all level surfaces

This stair nosing is suitable for all hard surfaces. It is installed on ceramics, wood, porcelain and terrazzo.

This stair nosing has a 10 mm face or riser, this means that the steps have to be level.

It is recommended to choose another profile, if the step edges are chipped or cracked, or in some cases where the stairs have a rolled edge.





B Height of

nosing 10 mm

SPECIFICATIONS

BASE MATERIAL Alloy: 6060, Temper: T5

FINISH Clear Anodised – 25Um/Anodised Black/Anodised Sovereign Gold

TREAD WIDTH 68 mm

FRONT DEPTH 10 mm

TREAD THICKNESS 4.8mm

INSERT TYPE Carborundum - Epoxy - Santoprene Rubber -Ripple

Trim

PRODUCT WARRANTY 2 year product warranty

INSERT SLIP RATING P5 classification (Highest available Carborundum)P4 Serrated

rubber and aluminium ripple trim

CODE COMPLIANCE AS1428.1-2021 Compliant

Check floor finish colour for luminance contrast requirements and

FIXING METHOD Screw of adhesive

APPLICATION Surface mounted on hard floor finishes – Concrete , Timber, porcelain, ceramics,

terrazzo



D Width of nosing 68 mm

A size of insert 54 mm







C width of

E size of

