

STAIR NOSING AUSTRALIA

STAIRNOSING 18 series-designed for thick flooring finishes


Stair Nosing Perth offer a comprehensive range of architecturally designed profiles to meet every demand, from heavy duty traffic in railway stations to the more general retail/office use, providing maximum pedestrian safety and WHS requirements.


This stair nosing is has generous rebates at the back and front to allow for thick flooring finishes.

This includes rubber, hardwood flooring, rubber backed vinyl plank, and any flooring acoustic flooring flooring finishes.

Additionally with its 10 mm face it complies with AS 1428 2009 standards







SPECIFICATIONS PRODUCT 18 series BASE MATERIAL Alloy: 6060, Temper: T5 Clear Anodised - 25Um/Anodised Black/Anodised Sovereign Gold TREAD WIDTH 82 mm FRONT DEPTH 10 mm TREAD THICKNESS 4.8mm INSERT TYPE Carborundum - Epoxy - Santoprene Rubber Aluminum Ripple trim 2 Years (As per Stair Nosing Perth's standard warranty PRODUCT WARRANTY INSERT SLIP RATING P4 classification for serrated rubber and aluminum ripple CODE COMPLIANCE trim and P5 classification for carborundum and epoxy. (Highest available) FIXING METHOD AS1428.1-2021 APPLICATION Check floor finish colour for luminance contrast requirements LRV [Light Reflective Values]



Inserts for 18 series

718 Anodised ripple trim P4


418 Carborundum


Surface mounted on hard floor finishes such as vinyl, rubber,

318 Santoprene Rubber P4









Screw fixed/or adhesive

drilled plugged and screwed with carpet

acoustic flooring and